

Job Safety Analysis(JSA)

Page1 of 4

JSA Title:	Forklift Operation		
Position Title:	Forklift Operator	JSA Covers:	_X_ Entire Job Partial Job
Position #:	123456	New or Revised:	_X_NewRevised
Employee Name:	John Q. Public	Analysis Completed by:	K. Sarah Sarah
Department:	Warehouse	Date Analysis Completed:	6/27/2019
Step or Task	Hazards	Control Measures	PPE / Training Required
1. Perform pre-operational safety and equipment check	Leaking, worn or damaged components that could cause faulty operation resulting in Impact or Compression to operator or bystander	If deficiencies are noted, do not operate the unit until all problems have been corrected	Forklift Operator Training
2. If LPG powered, turn gas valve on	Extreme cold (from leaking valve or hose) Impact (from leaking LPG hitting	Wear work gloves Turn valve slowly, wear safety	Gloves, Safety Glasses / Personal Protective Equipment Training
	eyes)	glasses	
3. Mount forklift	Falls from height	Maintain three points of contact when climbing into the cab	
4. Start engine	None foreseen	None	
5. Move the forklift to load(s) to be lifted	Impact (including struck by as a result of tip-over, running into obstacles and objects falling onto the operator and bystanders, as well as running into bystanders)	ALWAYS Yield to all other traffic and pedestrians. No passengers or riders are allowed in the forklift or to stand or be raised on the forks Wear your seatbelt at all times while you are in the forklift. Beep your horn before moving in reverse. Check clearance to ensure that you have enough—overhead, right, left, in front and behind (Watch the rear swing!).	

Sound horn and place fork lift in

	Compression (from tip-over and bystanders being caught between parts of the forklift and other objects)		
10. Dismount the forklift	Falls from height	Maintain three points of contact	
		when climbing down from the cab.	